

JTDC-B(Steel Shell) JTDC-C(Aluminum Shell) Portable Type Electronic Hanging Scale

Specification

- Accuracy Class:OIML III Grade. • Tare Range:100%F.S. • Zero Range:4%F.S.
- Safe Overload: 120%F.S. • Ultimate Overload:500%F.S.
- Overload Alarm:100%F.S.+9e • Battery:6V/10Ah • Battery Life:>80h
- Adapto:9V/1500mA • Remote Distance:≥10m • Temperature Range:-10°~+40°

Features

- High-quality alloy steel load receptor •Whole-steel anti-collision enclosure
- 56mm LED display
- High-duty bow shackle •High-duty eye hook •High capacity rechargeable battery
- Stainless steel button •Infrared remote controlling •Capacity:1000kg-10000kg



Capacity and Division

Model	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	H (mm)	N.W (kg)	Packing Size
JTDC-B/C-2	90	250	40	180	130	420	10.5	54×29×22
JTDC-B/C-3	90	250	40	180	130	420	11.5	54×29×22
JTDC-B/C-5	100	250	50	180	130	460	17.5	54×29×22
JTDC-B/C-10	130	250	70	180	130	560	27.5	69×35×26.5
JTDC-B/C-15	225	345	70	240	165	855	49	42.5×35.5×37
JTDC-B/C-20	225	345	85	240	165	920	56	42.5×35.5×37

