

# JTDC-E Rotary Type Electronic Handing Scale

## Specifications

- Manual zero range:4%F.S. • Peeled range:20%F.S.
- Stable time:≤10s • The alarm value of overload:100%F.S.+9e
- Charge of surety:125%F.S. • Ultimate load:400%F.S.
- Continuous use of time:≥50h • Source:60v/4.5Ah
- Charger:DC6V/1000mA • Operating temperature range:-10°~+40°
- Remote control receiver distance:10m • Remote power supply:7#(AAA) Battery 1.5v

## Features

- Zero/total/keep •Automatic zero tracking
- Overload alarm •Anti sway effect •Aluminium alloy shell
- 5 large digital tube display (30mm high letters)
- Dividing the value optional •The battery voltage automatic detection
- Low battery warning and auto power off function

## Capacity and Division

Model	The Max. scale (kg)	The Min. Scale (kg)	Divisi-on Value (kg)	Num-ber of Divisi- ons	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	H (mm)	N.W (kg)	Packing Size
JTDC-E-2	2000	20	1	2000	90	250	40	240	180	500	8	43×29×30.5
JTDC-E-3	3000	30	1	3000	90	250	40	240	180	500	8	43×29×30.5
JTDC-E-5	5000	50	2	2500	100	250	50	240	180	600	9	53×29×30.5
JTDC-E-10	10000	100	5	2000	120	250	60	240	180	700	17	68×29×30.5
JTDC-E-15	15000	150	5	3000	225	345	70	240	165	855	34	42.5×35.5×37
JTDC-E-20	20000	200	10	2000	225	345	85	240	165	920	40	42.5×35.5×37

