

JTTJ-C The Thinnest Hydraulic Jack

Technical parameters

Model	Capacity	Travel	Body height	Extension height	Cylinder bore	Outer diameter	Pressure
	(T)	(mm)	(mm)	(mm)	(mm)	(mm)	
JTTJ-C-50	5	6	26	32	35	50	63
JTTJ-C-100	10	11	35	46	45	70	63
JTTJ-C-200	20	11	42	53	60	92	63
JTTJ-C-300	30	13	49	62	75	102	63
JTTJ-C-500	50	16	57	73	100	127	63
JTTJ-C-750	75	16	66	82	115	146	63
JTTJ-C-1000	100	16	70	86	130	165	63
JTTJ-C-1500	150	16	84	100	160	205	63



JTTJ-B The Thinner Hydraulic Jack

Technical parameters

Model	Capacity	Travel	Body height	Extension height	Cylinder area	Oil capacity	Outer diameter	Net weight
	(T)	(mm)	(mm)	(mm)	(cm ²)	(cm ³)	(mm)	
JTTJ-B-50	5	6	33	39	6.4	4	64×52	1
JTTJ-B-100	10	11	43	54	14.5	16	83×66	1.4
JTTJ-B-200	20	11	52	63	28.6	31	100×84	3.1
JTTJ-B-300	30	13	59	72	42	55	128×105	4.5
JTTJ-B-500	50	16	67	83	62.1	99	145×128	6.8
JTTJ-B-750	75	16	80	96	102.7	164	188×158	11.4
JTTJ-B-1000	100	16	86	102	126.8	203	208×195	14.5
JTTJ-B-1500	150	16	100	116	198.1	277	250×220	26.3



JTTJ-A The Thin Hydraulic Jack

Technical parameters

Model	Capacity	Travel	Body height	Extension height	Cylinder area	Oil capacity	Outer diameter	Net weight
	(T)	(mm)	(mm)	(mm)	(cm ²)	(cm ³)	(mm)	
JTTJ-A-101	10	38	88	126	14.4	55	70	4.1
JTTJ-A-201	20	44	99	143	28.6	126	88	5
JTTJ-A-302	30	62	118	179	41.9	260	102	6.8
JTTJ-A-502	50	60	122	195	62.1	373	138	10.9
JTTJ-A-1002	100	57	141	198	126.9	723	188	22.7

