

Webbing Slings

Round slings



Webbing slings



JTWS-A Round Webbing Sling



The unique advantages of round sling:

1. Especially suitable for loading round objects.
2. The surface of round sling is smooth, does not cause damages to tender objects loaded.
3. Various loading methods, including dragging or pulling loaded object.
4. Various loading methods and load is bear evenly, enable the sling's usage life last longer.
5. High strength/weight ratio.
6. Anti-abrasion and anti-incision protection sleeve can be attached.
7. Has special label, working load is differentiated by colors according to international standard. Easy to identify even if the sling has been abraded.
8. Light and soft, can be used in small narrow space.
9. non-electric conductive, no danger of electric stroke.
10. In compliance with European Standard En1492-2:2000 and Chinese Standard JB/T8521-2007.

JTWS-A Round Sling's lifting method and maximum Safety Working Load parameter.

Model	Color	Max.SWL= Mode Coefficient P × Working Load Limit						Max. SWL of lifting method				Approx Width (mm)	Min Length (m)	Max Length (m)
		Single Max. Working Load Limit						2-Legs Max. Working Load Limit						
		Upright	Chocked	β				Upright 45°	Choked 45°	Upright 45°-60°	Choked 45°-60°			
				0°-7°	7°-45°	45°-60°	45°							
		1.0	0.8	2.0	1.4	1.0	0.7	1.4	1.12	1.0	0.8			
JTWS-A01	Violet	1000	800	2000	1400	1000	700	1400	1120	1000	800	50	1	100
JTWS-A02	Green	2000	1600	4000	2800	2000	1400	2800	2240	2000	1600	60	1	100
JTWS-A03	Yellow	3000	2400	6000	4200	3000	2100	4200	3360	3000	2400	70	1	100
JTWS-A04	Grey	4000	3200	8000	5600	4000	2800	5600	4480	4000	3200	75	1	100
JTWS-A05	Red	5000	4000	10000	7000	5000	3500	7000	5600	5000	4000	80	1	100
JTWS-A06	Brown	6000	4800	12000	8400	6000	4200	8400	6720	6000	4800	90	1	100
JTWS-A08	Blue	8000	6400	16000	11200	8000	5600	11200	8960	8000	6400	100	1	100
JTWS-A10	Orange	10000	8000	20000	14000	10000	7000	14000	11200	10000	8000	110	1	100
JTWS-A12	Orange	12000	9600	24000	16800	12000	8400	16800	13440	12000	9600	125	1	100
JTWS-A15	Blue	15000	12000	40000	28000	15000	14000	28000	22400	15000	12000	150	1	100
JTWS-A20	Orange	20000	16000	60000	42000	20000	21000	42000	33600	20000	16000	180	1	100
JTWS-A25	Orange	25000	20000	50000	35000	25000	17500	35000	28000	25000	20000	200	1	100
JTWS-A30	Orange	30000	24000	60000	42000	30000	21000	42000	33600	30000	24000	220	1	100
JTWS-A40	Orange	40000	32000	80000	56000	40000	28000	56000	44800	40000	32000	250	1	100
JTWS-A50	Orange	50000	40000	100000	70000	50000	35000	70000	56000	50000	40000	270	1	100
JTWS-A60	Orange	60000	48000	120000	84000	60000	42000	84000	67200	60000	48000	280	1	100
JTWS-A80	Orange	80000	64000	160000	112000	80000	56000	112000	89600	80000	64000	300	1	100
JTWSA100	Orange	100000	80000	200000	140000	100000	70000	140000	112000	100000	80000	320	1	100

