

JTR-TE04 JIS TYPE TURNBUCKLE

STEEL
STAINLESS STEEL 304or316



| Dia.Outside Length of Frame (mm) | Inside Dia of Eye (mm) | Weight Per pc (Kg) |
|--|---------------------------|--------------------------|
| 19×510 | 37 | 2.9 |
| 22×520 | 31×70 | 3.8 |
| 25×520 | 33×70 | 5.2 |
| 25×900 | 36×70 | 8.0 |
| 32×575 | 36×70 | 9.8 |
| 32×900 | 36×70 | . |
| 32×900 | 40×80 | . |

| Nominal Size(D) | | (1)Body Only | | | | | | (2)Eye&Eye | | | (3)Hook&Eye | | (4)Hook&Hook | | | (6)With Stubs | | | |
|--------------------|-------|--------------|----|-----|------|-----|------|------------|-----|-------|-------------|-------|--------------|------|-------|---------------|-----|------|-------|
| | | A | | B | | C | T.L | WPC | F | T.L | WPC | T.L | WPC | E | T.L | WPC | H | I | G |
| mm | in | mm | in | mm | in | mm | kg | mm | Ton | kg | Ton | kg | mm | Ton | kg | mm | mm | mm | kg |
| 6 | 1/4 | 100 | 4 | 78 | 11 | 1 | 0.08 | 10 | 0.1 | 0.116 | 0.04 | 0.114 | 9 | 0.04 | 0.112 | 80 | 50 | 5.3 | 0.112 |
| 8 | 5/16 | 125 | 5 | 100 | 12.5 | 1.2 | 0.15 | 12 | 0.2 | 0.22 | 0.08 | 0.218 | 9 | 0.08 | 0.215 | 100 | 63 | 6.9 | 0.22 |
| 9 | 3/8 | 150 | 6 | 120 | 12.5 | 1.5 | 0.17 | 16 | 0.5 | 0.3 | 0.15 | 0.293 | 11 | 0.15 | 0.29 | 130 | 75 | 8.3 | 0.273 |
| 12 | 1/2 | 200 | 8 | 164 | 18 | 2 | 0.29 | 20 | 2 | 0.58 | 0.35 | 0.585 | 16 | 0.35 | 0.57 | 150 | 100 | 11.2 | 0.51 |
| 16 | 5/8 | 250 | 10 | 202 | 21.5 | 3 | 0.52 | 22 | 3 | 1.07 | 0.7 | 1.05 | 19 | 0.7 | 1.03 | 180 | 125 | 14.2 | 0.95 |
| 19 | 3/4 | 300 | 12 | 250 | 25 | 4 | 0.85 | 28 | 4 | 1.77 | 1 | 1.78 | 20 | 1 | 1.77 | 220 | 152 | 17.2 | 1.62 |
| 22 | 7/8 | 325 | 13 | 269 | 28 | 5 | 1.17 | 33 | 5 | 2.55 | 1.5 | 2.58 | 21 | 1.5 | 2.6 | 250 | 165 | 20.3 | 2.34 |
| 25 | 1 | 400 | 14 | 285 | 32.5 | 6 | 1.69 | 35 | 6 | 3.79 | 2 | 3.77 | 26 | 2 | 3.72 | 270 | 175 | 23.3 | 3.27 |
| 32 | 1-1/4 | 400 | 16 | 310 | 45 | 8 | 3.51 | 36*70 | 10 | 7.6 | 3 | 7.52 | 34 | 3 | 7.44 | 300 | 200 | 29 | 6.52 |
| 38 | 1-1/2 | 450 | 18 | 350 | 55 | 10 | 5.08 | 40*80 | 15 | 13.5 | 4 | 12.8 | 35 | 4 | 22 | 330 | 225 | 38 | 13 |
| 44 | 1-3/4 | 500 | 20 | 386 | 57 | . | 9 | . | . | . | . | . | . | . | 22 | . | 250 | 44 | . |
| 50 | 2 | 550 | 22 | 420 | 65 | . | 11.5 | . | . | . | . | . | . | . | 29 | . | 275 | 50 | . |