

JTR-SE18 Australian Type Grade S Marine Towing Dee Shackle With Safety Pin

Product Code	Working Load Limit	Diameter Bow (mm)	Width Inside (mm)	Diameter Pin (mm)
JTR-SE1801	WLL0.33T	5	10	6
JTR-SE1802	WLL0.5T	6	12	8
JTR-SE1803	WLL0.75T	8	13	10
JTR-SE1804	WLL1T	10	17	11
JTR-SE1805	WLL1.5T	11	18	13
JTR-SE1806	WLL2T	13	21	16
JTR-SE1807	WLL3.25T	16	27	19
JTR-SE1808	WLL4.75T	19	32	22
JTR-SE1809	WLL6.5T	22	37	25
JTR-SE1810	WLL8.5T	25	43	29
JTR-SE1811	WLL9.5T	29	46	32
JTR-SE1812	WLL12T	32	52	35
JTR-SE1813	WLL13.5T	35	57	38
JTR-SE1814	WLL17T	38	60	41
JTR-SE1815	WLL25T	44	73	51
JTR-SE1816	WLL35T	51	83	57
JTR-SE1817	WLL55T	63	105	68
JTR-SE1818	WLL85T	76	127	83
JTR-SE1819	WLL120T	89	146	95
JTR-SE1820	WLL150T	102	165	108



Material	Body, Nut and Cotter Pin was carbon steel, BOLT was alloy steel
Construction	Quenched and Tempered
Standard	AS 2741-2002
Grade	S(6)