

JTR-SE16

Australian Type Rigging Hardware Grade S Dee Shackle

Product Code	Working Load Limit	Diameter Bow (mm)	Width Inside (mm)	Diameter Pin (mm)
JTR-SE1601	WLL0.33T	5	10	6
JTR-SE1602	WLL0.5T	6	12	8
JTR-SE1603	WLL0.75T	8	13	10
JTR-SE1604	WLL1T	10	17	11
JTR-SE1605	WLL1.5T	11	18	13
JTR-SE1606	WLL2T	13	21	16
JTR-SE1607	WLL3.25T	16	27	19
JTR-SE1608	WLL4.75T	19	32	22
JTR-SE1609	WLL6.5T	22	37	25
JTR-SE1610	WLL8.5T	25	43	29
JTR-SE1611	WLL9.5T	29	46	32
JTR-SE1612	WLL12T	32	52	35
JTR-SE1613	WLL13.5T	35	57	38
JTR-SE1614	WLL17T	38	60	41
JTR-SE1615	WLL25T	44	73	51
JTR-SE1616	WLL35T	51	83	57
JTR-SE1617	WLL55T	63	105	68
JTR-SE1618	WLL85T	76	127	83



Material	Body was carbon steel, Pin was alloy steel
Construction	Quenched and Tempered
Standard	AS 2741-2002
Grade	S(6)