

Specification: BS302 6×12+7FC

Nominal Diameter	Approx Weight	Nominal Tensile Strength	
		Minimum Breaking strength(KN)	
mm	kg/100m	1570N/mm ²	1770N/mm ²
2	1	-	1.48
3	2.26	-	3.33
4	4.02	-	5.92
5	6.28	-	9.25
6	9.04	-	13.3
7	12.3	-	18.1
8	16.1	21	23.7
9	20.3	26.6	30
10	25.1	32.8	37
11	30.2	39.4	44.3
12	36.1	47.3	53.3
14	49.2	64.3	-
16	64.3	84	-



6×12+7FC



6×24+7FC

Usage : Marine, General Industry, Lashing

Specification: DIN3068 6×24+7FC

Nominal Diameter	Approx Weight	Nominal Tensile Strength	
		Minimum Breaking strength(KN)	
mm	kg/100m	1570N/mm ²	1770N/mm ²
6	11.45	-	17.9
7	15.6	-	24.3
8	20.4	28.2	31.8
9	25.8	35.6	40.1
10	31.8	44	49.6
11	38.5	53.2	-
12	45.8	63.3	-
13	53.8	74.3	-
14	62.4	86.2	-
16	81.5	113	-
18	103	143	-
20	127	176	-
22	154	213	-
24	183	253	-
26	215	297	-