


Specification: DIN3066 6×37+FC, 6×37+WSC or IWRC


Nominal Diameter	Approx Weight		Nominal Tensile Strength					
			Minimum Breaking strength(KN)					
	kg/100m		1570N/mm ²		1770N/mm ²		1960N/mm ²	
mm	FC	IWRC	FC	IWRC	FC	IWRC	FC	IWRC
5	8.56	9.53	-	-	13.1	14.1	14.5	15.6
6	12.5	13.7	-	-	18.8	20.3	20.8	22.5
7	17	18.6	-	-	25.6	27.6	28.3	30.6
8	22.1	24.4	29.6	32	33.4	36.1	37	40
9	28	30.8	37.5	40.5	42.3	45.7	44.6	50.6
10	34.6	38.1	46.3	50	52.2	56.4	57.8	62.5
11	41.9	46.1	56	60.5	63.1	68.2	69.9	75.5
12	49.8	54.8	66.6	72	75.1	81.2	83.2	89.9
13	58.5	64.3	78.2	84.5	88.2	95.2	97.7	105.4
14	67.8	74.6	90.7	98	102	110	112.9	121.8
16	88.6	97.4	118	128	134	144	148.4	159.5
18	112	123	150	162	169	183	187.1	202.6
20	138	152	185	200	209	225	-	-
22	167	184	224	242	253	273	-	-
24	199	219	267	288	301	325	-	-
26	234	257	313	338	353	381	-	-
28	271	298	363	392	409	442	-	-
30	311	343	416	430	469	508	-	-
32	354	390	474	512	534	577	-	-
34	400	440	535	578	603	652	-	-
36	448	493	600	648	676	730	-	-
38	500	550	668	723	-	-	-	-
40	554	609	741	800	-	-	-	-
44	670	737	896	968	-	-	-	-
48	797	878	1070	1150	-	-	-	-



6×37+FC




6×37+WSC



6×37+IWRC

Specification: DIN3058 6×19(S)+FC 6×19(S)+ IWRC, 6×19(W)+FC, 6×19(W)+ IWRC


Nominal Diameter	Approx Weight		Nominal Tensile Strength			
			Minimum Breaking strength(KN)			
	kg/100m		1570N/mm ²		1770N/mm ²	
mm	FC	IWRC	FC	IWRC	FC	IWRC
6	13.4	14.8	-	-	21.1	22.8
7	18.3	20.1	-	-	28.7	31
8	23.8	26.2	33.2	35.9	37.5	40.5
9	30.2	33.2	42.1	45.35	47.4	51.2
10	37.3	41	52	56.1	58.6	63.8
11	45.1	49.6	62.9	67.9	70.9	76.5
12	53.7	59	74.8	80.8	84.3	91.1
13	63	69.3	87.8	94.8	99	107
14	73.1	80.4	102	110	115	124
15	83.9	92.3	117	126	132	142
16	95.5	105	133	144	150	162
17	108	119	150	162	169	183
18	121	133	168	182	190	205
19	135	148	188	203	211	228
20	149	164	208	224	234	253
22	181	198	251	272	283	306
24	215	236	299	323	337	364
26	252	277	351	379	396	428
28	292	321	407	440	459	496
30	336	369	467	505	-	-
32	382	420	532	575	-	-
36	483	531	673	727	-	-



8×19 (S) +FC



8×19 (W) +FC



8×19 (S) +IWRC



8×19 (W) +IWRC